# Gin 90 Series

Gin 90 Bar

Gin 90 Low

Gin 90 Chat

Gin 90 Series Design features

ecosmart⁺ Fire

1. Fluid™ Concrete Finish
Incredibly strong yet relatively lightweight, EcoSmart's concrete products incorporate revolutionary Fluid Concrete Technology. Fluid features a stain and impact-resistant barrier that protects the concrete from environmental weathering – even under extreme conditions and long UV exposure.

Premium Teak Wood Finish
Classed as the most premium wood on the planet, teak is the strongest, most durable hardwood available. Teak contains a natural oi n c wate a tnisros

Included Accessories

Jerry Can with Safety Spout & e-NRG bottle adaptor

Lighting Rod & Lighter

XL Baffles

Black Glass Charcoal

Optional Accessories

Glass Fire Screen

Outdoor Cover

Natural (Gin 90 Bar)

Graphite (Gin 90 Dining)

Bone (Gin 90 Chat)

Teak (Gin 90 Low)

ecosmar⁺
F i r e

Gin 90 Bar Specifications

Combining the functionality of a bar-height table with an integrated, elongated flame, Gin 90 Bar fire table is ideal for encouraging casual conversation.

|		
Application	Indoor[1] & Outdoor	
Surround Colours	Natural ESF.O.GIN.90.B.NA	Graphite ESF.O.GIN.90.B.GH
	Bone ESF.O.GIN.90.B.BO	Teak ESF.O.GIN.90.B.TN
Burner Colours	Stainless Steel	Black
Materials	Fluid Concrete or Teak Wood Surround, Grade 304 Stainless Steel Burner, with optional Black Ceramic Coating	
Approx. Weight	Concrete 221.2kg [486.7lbs] Teak 124.7kg [274.4lbs] Weight includes burner and black glass charcoal.	
Fuel Type	e-NRG Bioethanol / **e-NRG.com**	

FOR MORE INFORMATION PLEASE REFERENCE THE CLEARANCE & INSTALLATION MANUAL

Gin 90 Dining Specifications

A clever, dual-purpose fire dining table with room for dining chairs, the Gin 90 Dining features the XL900 Burner as its centrepiece.

Burner Ventilation and Efficiency*

Dimensions L x W x H mm/in	Compatible Burner	Fuel Capacity	Heats on Average (Indoors)	Thermal Output Net (MAX)	Approx. Burn Time	Minimum Room Size
2272 x 1098 x 745 89.4 x 43.2 x 29.3	XL900	9 L [2.4 Gals]	Over 60 m² [645 ft²]	16 MJ/h 15,000 BTU/h 4.4 kW	8 - 13 hours	110 m³ [3,884 ft³]

Application	Indoor[1] & Outdoor
Surround Colours	Natural ESF.O.GIN.90.D.NA Graphite ESF.O.GIN.90.D.GH Bone ESF.O.GIN.90.D.BO Teak ESF.O.GIN.90.D.TN
Burner Colours	Stainless Steel Black
Materials	Fluid Concrete or Teak Wood Surround, Grade 304 Stainless Steel Burner, with optional Black Ceramic Coating
Approx. Weight	Concrete 203.2kg [447.1lbs] Teak 119.7kg [263.4lbs] Weight includes burner and black glass charcoal.
Fuel Type	e-NRG Bioethanol / **e-NRG.com**

Line drawings show concrete models with the optional Glass Fire Screen accessory.

[44.2] 1122

[35.1] 893   [29.3] 745   [24.5] 621

[89.4] 2272

[12.4] 316   [64.6] 1640   [12.4] 316

[43.2] 1098   [12.6] 319   [18.1] 460   [12.6] 319

*These values are indicative only and may vary depending on the model purchased, installation, and the seasonal resource used to manufacture e-NRG.
This model comes with fixing brackets for permanently locating into a fixed position.
[1]For Indoor Use, additional parts are required. Your chosen application is the ONLY application the model can be used in due to modified configuration of the model. Please advise your Sales Representative at time of purchase so that the product can be configured accordingly.
This model complies with existing standards in the USA, Europe, UK and Australia. UL Listed, EN 16647 BSI Certified ACCC Safety Mandate compliant. To comply with EN 16647 the Indoor Safety Tray must be installed before operating indoors.

FOR MORE INFORMATION PLEASE REFERENCE THE CLEARANCE & INSTALLATION MANUAL

**Freestanding Fire Tables**

Gin 90 Chat Specifications

ecosmart⁺
Fire

The warmth and aesthetic appeal of an open flame combined with a cleverly engineered piece of fire furniture are the hallmarks of the Gin 90 Chat fire pit table.

Burner Ventilation and Efficiency*

| Dimensions L x W x H mm/in	Compatible Burner	Fuel Capacity	Heats on Average (Indoors)	Thermal Output Net (MAX)	Approx. Burn Time	Minimum Room Size
2272 x 1098 x 595 89.4 x 43.2 x 23.4	XL900	9 L [2.4 Gals]	Over 60 m² [645 ft²]	16 MJ/h 15,000 BTU/h 4.4 kW	8 - 13 hours	110 m³ [3,884 ft³]

|	
Application	Indoor[1] & Outdoor
Surround Colours	Natural ESF.O.GIN.90.C.NA Graphite ESF.O.GIN.90.C.GH Bone ESF.O.GIN.90.C.BO Teak ESF.O.GIN.90.C.TN
Burner Colours	Stainless Steel Black
Materials	Fluid Concrete or Teak Wood Surround, Grade 304 Stainless Steel Burner, with optional Black Ceramic Coating
Approx. Weight	Concrete 188.8kg [415.4lbs] Teak 110.7kg [243.6lbs] Weight includes burner and black glass charcoal.
Fuel Type	e-NRG Bioethanol / **e-NRG.com**

FOR MORE INFORMATION PLEASE REFERENCE THE CLEARANCE & INSTALLATION MANUAL

Gin 90 Low Specifications

True to its name, the Gin 90 Low table is a low-set fire pit table that's been created to be a multi-functional piece of furniture for indoors or outside.

Burner Ventilation and Efficiency*

| Dimensions L x W x H mm/in	Compatible Burner	Fuel Capacity	Heats on Average (Indoors)	Thermal Output Net (MAX)	Approx. Burn Time	Minimum Room Size
2272 x 1098 x 345 89.4 x 43.2 x 13.6	XL900	9 L [2.4 Gals]	Over 60 m² [645 ft²]	16 MJ/h 15,000 BTU/h 4.4 kW	8 - 13 hours	110 m³ [3,884 ft³]

Application	Indoor[1] & Outdoor
Surround Colours	Natural ESF.O.GIN.90.L.NA Graphite ESF.O.GIN.90.L.GH Bone ESF.O.GIN.90.L.BO Teak ESF.O.GIN.90.L.TN
Burner Colours	Stainless Steel Black
Materials	Fluid Concrete or Teak Wood Surround, Grade 304 Stainless Steel Burner, with optional Black Ceramic Coating
Approx. Weight	Concrete 171.1kg [376.5lbs] Teak 91.7kg [201.8lbs] Weight includes burner and black glass charcoal.
Fuel Type	e-NRG Bioethanol / **e-NRG.com**

Line drawings show concrete models with the optional Glass Fire Screen accessory.

[44.2] 1122
[19.4] 493
[13.6] 345
[8.7] 221

[89.4] 2272
[12.4] 316
[64.6] 1640
[12.4] 316
[12.6] 319
[43.2] 1098
[18.1] 460
[12.6] 319

*These values are indicative only and may vary depending on the model purchased, installation, and the seasonal resource used to manufacture e-NRG.

This model comes with fixing brackets for permanently locating into a fixed position.

[1]For Indoor Use, additional parts are required. Your chosen application is the ONLY application the model can be used in due to modified configuration of the model. Please advise your Sales Representative at time of purchase so that the product can be configured accordingly.

This model complies with existing standards in the USA, Europe, UK and Australia. UL Listed, EN 16647 BSI Certified ACCC Safety Mandate compliant. To comply with EN 16647 the Indoor Safety Tray must be installed before operating indoors.

FOR MORE INFORMATION PLEASE REFERENCE THE CLEARANCE & INSTALLATION MANUAL